

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max.Air Pressure (KPa)	Max.Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	40"	205/40R17	XL	BSW	7.5	-	84W	500	1102	340	50	7.8	212	596
2	45"	205/45R16	SL	BSW	7.0	-	83V	487	1074	350	51	7.8	206	590
3		205/45R16	XL	BSW	7.0	-	87W	545	1201	340	50	7.8	206	590
4	50"	195/50R15	SL	BSW	6.0	-	82V	475	1047	350	51	7.8	201	577
5		205/50R16	SL	BSW	6.5	-	87V	545	1201	350	51	7.8	214	612
6	55"	195/55R15	SL	BSW	6.0	-	85H	515	1135	350	51	7.8	201	595
7		195/55R15	SL	BSW	6.0	-	85V	515	1135	350	51	7.8	201	595
8		195/55R16	XL	BSW	6.0	-	91H	615	1356	340	50	7.8	201	620
9		195/55R16	XL	BSW	6.0	-	91V	615	1356	340	50	7.8	201	620
10		205/55R16	SL	BSW	6.5	-	91H	615	1356	350	51	7.8	214	632
11		205/55R16	SL	BSW	6.5	-	91V	615	1356	350	51	7.8	214	632
12	60"	195/60R15	SL	BSW	6.0	-	88H	560	1235	350	51	7.8	201	615
13		195/60R15	SL	BSW	6.0	-	88V	560	1235	350	51	7.8	201	615
14		205/60R14	SL	BSW	6.0	-	88V	560	1235	350	51	7.8	209	602
15		205/60R15	SL	BSW	6.0	-	91H	615	1356	350	51	7.8	209	627
16		205/60R15	SL	BSW	6.0	-	91V	615	1356	350	51	7.8	209	627
17		205/60R16	SL	BSW	6.0	-	92H	630	1389	350	51	7.8	209	652
18		205/60R16	SL	BSW	6.0	-	92V	630	1389	350	51	7.8	209	652
19		205/60R16	XL	BSW	6.0	-	96V	710	1565	340	50	7.8	209	652
20		215/60R16	SL	BSW	6.5	-	95H	690	1521	350	51	7.8	221	664
21		215/60R16	SL	BSW	6.5	-	95V	690	1521	350	51	7.8	221	664
22		215/60R16	XL	BSW	6.5	-	99V	775	1709	340	50	7.8	221	664
23		225/60R16	SL	BSW	6.5	-	98H	750	1653	350	51	7.8	228	676
24		225/60R16	XL	BSW	6.5	-	102V	850	1874	340	50	7.8	228	676
25	65"	195/65R15	SL	BSW	6.0	-	91H	615	1356	350	51	7.8	201	635
26		195/65R15	SL	BSW	6.0	-	91V	615	1356	350	51	7.8	201	635
27		205/65R15	SL	BSW	6.0	-	94H	670	1477	350	51	7.8	209	647
28		205/65R15	SL	BSW	6.0	-	94V	670	1477	350	51	7.8	209	647
29	70"	195/70R14	SL	BSW	6.0	-	91T	615	1356	350	51	7.8	201	630